




LED HIGH BAY LIGHT 24W/30W/60W/80W/120W/160W



LED HIGH BAY LIGHT

Product Name	HIGH BAY LIGHT		HIGH BAY LIGHT		HIGH BAY LIGHT	
Item No.	NKX-32/1-024/2-FD		NKU-64/4-060/2-FD		NKU-20/25-120/4-FD	
	NKX-32/1-030/2-FD		NKU-64/4-080/2-FD		NKU-20/25-160/4-FD	
Input Power	24W/30W		60W/80W		120 W/160 W	
Luminous Flux	2112 LM/2400 LM		5280 LM/7040 LM		10560LM/14080 LM	
Luminous Efficiency	88 LM/W		88 LM/W		88 LM/W	
Input Voltage	100V/110V/120V/220V/230V/240VAC/347VAC		90 VAC ~ 260VAC/277 VAC/347VAC		90 VAC ~ 260VAC/277 VAC/347VAC	
Frequency	50 Hz / 60 Hz		50 Hz / 60 Hz		50 Hz / 60 Hz	
AC Power Factor	AC 55%		AC 99%		AC 99%	
DC Power Efficiency	AC 94%		AC 94%		AC 94%	
Beam Angle	73°(50%)		73°(50%)		73°(50%)	
Color Temperature	2700K - 6500K		2700K - 6500K		2700K - 6500K	
Color Rendering Index	Ra>80		Ra>80		Ra>80	
Working Temperature	-40°C ~ +50°C		-40°C ~ +50°C		-40°C ~ +50°C	
Housing&Lampshade	Aluminium Alloy+PC		Aluminium Alloy+PC		Aluminium Alloy+PC	
IP Rating	IP20	IP55	IP20	IP55	IP20	IP55
Outline Size	ø317*325(mm)		ø317*408(mm)[Hook]	ø 317*365(mm)[Sucker]	ø500*611(mm)[Hook]	ø500*561(mm)[Sucker]
Package Size	360*360*410(mm)		360*360*410(mm)		560*560*585(mm)	
Gross/Net Weight	2.64kg/0.92kg		3.2kg/1.36kg		7.5kg/4.1kg	
Installation Method	Sucker		Hook with a stick Sucker with a stick		Hook with a stick Sucker with a stick	
Dimension						
Application	Factory line, warehouse, cold store, highway toll stations, gas stations, supermarkets, exhibition halls, stadiums etc.					

Products features

- High voltage, low current, energy-saving, environment friendly, healthy and saving money;
- Use aluminium alloy material, easy to transport, have uniform light and high effective reflection;
- With PC material, glittering and translucent, easy to transport;
- It's available to hang it up with hook or hanging plate, as well as add pole between the lamp holder and hanging plate(or hook) per requests.



Light Distribution Curve

